

800x1600

PGVT

HIGH GLOSS

Business aside, we are very much aware of the human factors involved in our business. We are aware that our customers and employees expectation and deserve only the best. Awareness of these underlying issues lies deep within the fabric of our day-today work. We are also very much concerned about environmental factors.

We hope the above details will be in line.

If you need more details always feel free to contact with us.



To launch innovative and world class products to help customers realize dreams. To supply products of the highest quality, creating industry benchmark. Be fast and flexible, to be able to grasp opportunities in the fast changing world. To be transparent and fair to customers, suppliers, and employees in all our dealings.



We always believe in innovation, new creation.
as "Success demand creativity & innovativeness."
Development of designs done in association with customers as a partner to meet their requirements.
In very short period, managed to earn huge reputation and popularity in the industry just because of the fact that it achieved to satisfy the exact needs of clients.
We have well-managed marketing & distribution channel for even distribution of our tiles nationally and in overseas market. We deliver excellent customer service and that what helped us in creating success and a niche presence in the industry as notable exporter of Indian tiles.

HIGH GLOSS COLOR SHADES







ELECRTIC BLUE



EMPERADOR DARK



PEBBLE DECK



PORTORA NEW

SIZES AND THICKNESS



TECHNICAL CHARACTERISTICS



Waterproof Surface



Respectful Environment



Wear Resistance



Chemical Resistance



Impact Resistance



Lightweight



Scratch Resistance



Flexural Strength

ARMANI ORO

800x1600mm Size:































AQUARIUM BLUE

Size: 800x1600mm




















fi







AZUL CANDY

800x1600mm Size:
































BLACK BRESCIA

Size: 800x1600mm























BLACK POTORO

800x1600mm Size:


















frost proof





BLUE BRECIA

Size: 800x1600mm















ire oof









CALCUTTA INFINITY

800x1600mm Size:

HIGH GLOSS Finish:





CRYSTAL GLAZED





















ELECRTIC BLUE

800x1600mm Size:























EMPERADOR DARK

Size: 800x1600mm

























ESTRADA

Size: 800x1600mm
















fire proof

frost proof






FRAPPUCCINO NATURAL

800x1600mm Size:





















LUSTRO VENEER

Size: 800x1600mm



















fire proof







PEBBLE DECK

Size: 800x1600mm

















ire oof







PIETRA NATURAL


800x1600mm Size:

HIGH GLOSS Finish:





CRYSTAL GLAZED




















frost proof



PORTORA NEW

800x1600mm Size:
































RAINBOW ROCK

Size: 800x1600mm





















f p









RIVER BLACK

Size: 800x1600mm

























SAINT LORENT EDIT

800x1600mm Size:

















durable over time

frost proof





SAPPHIRE BLACK

Size: 800x1600mm






























TRAVERTINO ARANCIA

Size: 800x1600mm





























ULT PANTHER BLACK

800x1600mm Size:

ULT Finish:





























TECHNICAL SPECIFICATIONS

CHARACTERISTICS	STANDARD AS PER ISO-13006/EN14411	MEAN VALUE OF OUR PGVT	TEST METHOD						
GROUP BIA COR FGV I REGULATORY PROPERTIES									
Deviation in length & width	±0.5 %	±0.1 %	ISO-10545-2						
Deviation in thickness	±5.0 %	±4.0 %	ISO-10545-2						
Straightness in side	±0.5 %	±0.1 %	ISO-10545-2						
Rectangularity	±0.6 %	±0.1 %	ISO-10545-2						
Surface flatness	±0.5 %	±0.2 %	ISO-10545-2						
Color difference	Unaltered	No change	ISO-10545-16						
Glossiness	As per mfg.	Min. 90%	GLOSSOMETER						
SURFACE MECHANICAL PROPERTIES									
Water absorption	< 0.50 %	< 0.05 %	ISO-10545-3						
Apparent density	> 2.0 g/cc	> 2.10 g/cc	DIN 51082						
MASSIVE MECHANICAL PROPERTIES									
Modulus of rupture	Min. 35 N/mm²	Min. 40 N/mm²	ISO-10545-4						
Breaking strength	Min. 1300 N	Min. 2000 N	ISO-10545-4						
Impact resistance	As per mfg.	Min. 0.55	ISO-10545-5						
SURFACE MECHANICAL PROPERTIES									
Surface abrasion resistance	As per mfg	Min. Class-3	ISO-10545-7						
MOH's hardness	As per mfg	Min. 4	EN 101						
THERMO HYDROMETRIC PROPERTIES									
Frost resistance	No damage	No damage	ISO-10545-12						
Thermal shock resistance	No damage	No damage	ISO-10545-9						
Moisture expansion	Nil	Nil	ISO-10545-10						
Thermal expansion (COE)	Max. 9.0x10 ⁻⁶	Max. 6.5x10 ⁻⁶	ISO-10545-8						
Crazing resistance	As per mfg.	Min. 10 Cycle	ISO-10545-11						
CHEMICAL PROPERTIES									
Chemical resistance	No damage	No damage	ISO-10545-13						
Stain resistance	Resistant	Resistant	ISO-10545-14						
SAFETY PROPERTIES									
Slip resistance	As per mfg.	> 0.40	ISO-10545-17						
Fire resistance	As per mfg.	Fireproof	N. A.						
Lead & Cadmium given off by glazed tiles	As per mfg.	Doesn't yield Pb & Cd	ISO-10545-15						

PACKING DETAILS

Sr. No.	Size	Thickness (approx*)	Pieces / Box	Area / Box (approx*)		Packing
1	80x160cm	9 to 9.5 mm	2 pcs.	2.56 sq. mtr.	27.55 sq. ft.	Box

AARTOS INTERNATIONAL LLP

Head Office

Office No. S16-S17, A Wing, 2nd floor, Ishan Cera Zone, Lalpar Morbi - 363 642, Gujarat, India.

Branch Office

Ruda - 1, Plot No. 12, Kalawad Road, Rajkot - 360 005, Gujarat, India.

☑: aartosinternational@gmail.com 🔞: +91 98980 92843