



SUGAR SERIES

Business aside, we are very much aware of the human factors involved in our business. We are aware that our customers and employees expectation and deserve only the best. Awareness of these underlying issues lies deep within the fabric of our day-today work. We are also very much concerned about environmental factors.

We hope the above details will be in line.

If you need more details always feel free to contact with us.



To launch innovative and world class products to help customers realize dreams. To supply products of the highest quality, creating industry benchmark. Be fast and flexible, to be able to grasp opportunities in the fast changing world. To be transparent and fair to customers, suppliers, and employees in all our dealings.



We always believe in innovation, new creation.
as "Success demand creativity & innovativeness."
Development of designs done in association with customers as a partner to meet their requirements.
In very short period, managed to earn huge reputation and popularity in the industry just because of the fact that it achieved to satisfy the exact needs of clients.
We have well-managed marketing & distribution channel for even distribution of our tiles nationally and in overseas market. We deliver excellent customer service and that what helped us in creating success and a niche presence in the industry as notable exporter of Indian tiles.

#### SUGAR COLOR SHADES







**ANLAYA GREY** 



S 2029 DS SUGAR



DS SUGAR 010



S 2004 ZURIC DARK

#### SIZES AND THICKNESS





#### TECHNICAL CHARACTERISTICS



Waterproof Surface



Respectful Environment



Wear Resistance



Chemical Resistance



Impact Resistance



Lightweight



Scratch Resistance



Flexural Strength

Finish: SUGAR





# CRYSTAL GLAZED









Anlaya Grey






















Platinum White

























S-1111











easy to clean

dura e over t

fr













Sparta Black























Sparta Gre


















Zuric Dark















frost













S-2026























S-2027























S-2028











easy

durable over time

frost







S-2029 Ds Sugar




























Ds Sugar 010














fire













2033 Ds Sugar 009







fire



\_\_\_\_\_













Ds Sugar 010 006
























Ds Sugar 010 004











easy to clean

eco

fro













S-2037

























S 2038 Ds Sugar 003























Ds Sugar 010 005

















S-2040 Ds Sugar 009













.

Finish: SUGAR





## CRYSTAL GLAZED









Satuario 2











CHARACTERISTIC	STANDARD AS PER ISO-13006/EN14411 GROUP BLA	MEAN VALUE OF AARTOS MIRROR	TEST METHOD
REGULATORY PROPERTIES			
Deviation in Length & Width	±0.5%	±0.1%	ISO-10545-2
Deviation in Thickness	±5.0%	±4.0%	ISO-10545-2
Straightness in Side	±0.5%	±0.1%	ISO-10545-2
Rectangularity	±0.5%	±0.1%	ISO-10545-2
Surface Flatness	±0.5%	±0.2%	ISO-10545-2
Color Difference	Unaltered	No Change	ISO-10545-16
Glossiness (ONLY FOR PGVT)	As Per Mfg.	Min 90%	GLOSSMETER
STRUCTURAL PROPERTIES			
Water Absorption	< 0.50%	< 0.05%	ISO-10545-3
Apparent Density	> 2.0 g/cc	> 2.10 g/cc	DIN 51082
MASSIVE MECHANICAL PRO	DPERTIES		
Modulus of Rupture	Min. 35 N/mm²	Min. 40 N/mm²	ISO-10545-4
Breaking Strength	Min. 1300 N	Min. 2000 N	ISO-10545-4
Impact Resistance	As Per Mfg.	Min. 0.55	ISO-10545-5
SURFACE MECHANICAL PRO	OPERTIES		
Surface Abrasion Resistance	As Per Mfg.	Min. Class-3	ISO-10545-7
MOH's Hardness	As Per Mfg.	Min. 4	EN 101
THERMO HYGROMETRIC PR	OPERTIES		
Frost Resistance	No Damage	No Damage	ISO-10545-12
Thermal Shock Resistance	No Damage	No Damage	ISO-10545-09
Moisture Expansion	Nil	Nil	ISO-10545-10
Thermal Expansion (COE)	Max. 9.0 x 10-6	Max. 6.5 x 10 <sup>-6</sup>	ISO-10545-8
Crazing Resistance	As Per Mfg.	Min. 10 Cycle	ISO-10545-11
CHEMICAL PROPERTIES			
Chemical Resistance	No Damage	No Damage	ISO-10545-13
Stain Resistance	Resistance	Resistance	ISO-10545-14
SAFETY PROPERTIES			
Slip Resistance	As Per Mfg.	> 0.40	ISO-10545-17
Fire Resistance	As Per Mfg.	Fireproof	N. A.
Lead & Cadmium Given Off		Does Not Yield	

# **Packaging Detail**

Size	Thickness (approx.)	Tiles Per Box	Coverage Area	Wt.Kgs. / Box
600x600 MM	8.5 MM	4 Pcs.	1.44 Sq. Mtr.	27.50









### **AARTOS INTERNATIONAL LLP**

Head Office

Office No. S16-S17, A Wing, 2nd floor, Ishan Cera Zone, Lalpar Morbi - 363 642, Gujarat, India.

**Branch Office** 

Ruda - 1, Plot No. 12, Kalawad Road, Rajkot - 360 005, Gujarat, India.

☑: aartosinternational@gmail.com 🔞: +91 98980 92843